



IS standard



GROWING TOGETHER

RM 500



PRODUCT DATA SHEET



Radial



182

RM 500



RM 500 is a steel-belted radial tire suitable for harvester implement applications. It features a strong casing and a special tread design providing high load capacity and particular cut-and-chip resistance. Thanks to its large footprint, RM 500 ensures great pressure distribution on the ground with reduced soil compaction in addition to excellent traction.

Technologies



Steel Belted

Performance



High Load Capacity



Stability



Traction



High Puncture Resistance

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	500/70 R 24	167 A8/155 A8	W 16 L	W 15 L	502	1310	572	3907	625	SB
	500/85 R 24	182 A8/170 A8	W 16 L	W 15 L	520	1460	622	4382	700	SB
	500/85 R 24	182 A8/170 A8	W 16 L	W 15 L	520	1460	622	4382	700	SB
Ø 28"	500/80 R 28	176 A8/164 A8	W 16 L	W 15 L	503	1495	635	4355	700	SB
	600/65 R 28	168 A8/156 A8	W 18 L	W 20 L	590	1486	640	4340	700	SB
	600/65 R 28	177 A8/165 A8	W 18 L	W 20 L	590	1486	640	4340	700	SB
Ø 30"	500/85 R 30	176 A8/164 A8	W 16 L	W 15 L	535	1610	674	4745	775	SB

SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index