



US standard



GROWING TOGETHER

# SIERRAMAX

ATV & GO KART TIRES



PRODUCT DATA SHEET



Radial



58



**SIERRA MAX**  
ATV & GO KART TIRES

SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

**Technologies**



M+S

**Performance**



Comfort



Sport



Traction

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	
				Rec.	Alt.								
Ø 12"	94064786	AT 25 X 8 R 12	43 N	6.5	-	8.1	25.2	11.5	74.8	25	22	STD	
	94064793	AT 25 X 10 R 12	50 N	8.0	-	10.2	25.2	11.6	75.7	25	26	STD	
	94515660	AT 26 X 9 R 12	49 N	7.0	-	9.1	26.0	12.0	79.1	25	25	STD	
		<b>NEWSIZE</b>											
	94515684	AT 26 X 10 R 12	52 N	8.0	-	10.2	26.0	12.0	79.0	25	28	STD	
		<b>NEWSIZE</b>											
Ø 14"	94515707	AT 26 X 11 R 12	55 N	9.0	-	11.0	26.0	11.9	78.5	25	29	STD	
		<b>NEWSIZE</b>											
	94515721	AT 26 X 12 R 12	58 N	9.5	-	12.0	26.0	11.9	78.7	25	31	STD	
		<b>NEWSIZE</b>											
Ø 14"	94052325	AT 26 X 9 R 14	48 N	7.00	-	9.1	26.6	12.1	78.9	25	25	STD	
	94052332	AT 26 X 11 R 14	54 N	9.00	-	11.0	26.6	12.2	79.8	25	30	STD	
	94052615	AT 27 X 9 R 14	50 N	7.00	-	9.1	27.6	12.4	81.5	25	27	STD	
	94052622	AT 27 X 11 R 14	56 N	9.00	-	11.0	27.6	12.5	82.3	25	32	STD	

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference