



AW 726

Description

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Trailer



Version	ARAMID BELTED
Tire Type	TL
Tyre size	11.5/80-15.3
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	300
OD (IS) (mm)	855
SLR (IS) (mm)	363
RC (IS) (mm)	2531
Rim Rec	9.00
ECE	E11-106R-0010913

Load Capacity (IS)

km/h / bar	05:20:00																
10 FR	3400																
25 FR	2890																
30 FR	2720																
40 FR	2430																
10 DW	2380																
25 DW	2025																
30 DW	1905																
40 DW	1700																

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..