



DON 2000

Description

DON 2000 is a suitable for transport operations with trailers and light trucks both on and off the road. It ensures extra durability along with high performance during the entire product life-cycle.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ▪ Light Truck



Version	STANDARD
Tire Type	TT
Tyre size	9.00-20
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	270
OD (IS) (mm)	1048
Rim Rec	7.0
Rim Alt	6.5; 7.5

Load Capacity (IS)

km/h / bar	7.95	7.25
100 LS	2650	-
100 LD	-	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..