



AW 729

Description

AW 729 is an agricultural tire specifically designed for transport, hay harvesting, baling and soil tillage applications. Its rounded shoulder and three central grooves tread design provide low soil compaction and avoids damages to the field. AW 729 is the ideal tire for modern farming, and it is suited for both on-and-off-the- road usage.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Baler



Version

STANDARD

Tire Type

TL

Tyre size

340/55-16

LI/SS

Dimensions IS Standard

SW (IS) (mm)	343
OD (IS) (mm)	785
SLR (IS) (mm)	358
RC (IS) (mm)	2358
Rim Rec	11.0
ECE	E11-106R-006421

Load Capacity (IS)

km/h / bar	3.20
10 FR	2885
25 FR	2450
30 FR	2305
40 FR	2060
10 DW	2030
25 DW	1725
30 DW	1625
40 DW	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..