



## EARTHMAX SR 425



### Description

EARTHMAX SR 425 is an All Steel radial tire designed for transport applications, both on and off the road, as well as mining operations. It features enhanced durability and mileage along with high load capacity thanks to the strong steel-belted construction and casing. The block-type tread pattern provides excellent traction. In addition, EARTHMAX SR 425 ensures excellent riding comfort, less driving fatigue and superior handling.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ On/Off Truck

Version	STANDARD
Tire Type	TT
Tyre size	11.00R20
LI/SS	152/149;J

## Dimensions IS Standard

OD (IS) (mm)	1102
Rim Rec	8.00
Rim Alt	8.50

## Load Capacity (IS)

km/h / bar	8.30
100 Load Single	3550
100 Load Dual	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..