



## SAND KING

### Description

SAND KING is a block pattern tyre specially designed for trailers in transport applications. It provides excellent traction on sandy surfaces and best ground contact.

### UM

US Standard

### Construction

◇ Bias

### Machinery

Industrial & Construction ■ Trailer



Version	STANDARD
Tyre Type	TT
Tyre size	7.50-16
LI/SS	

## Dimensions US Standard

USA Code	94046508
SW (in)	8.5
OD (in)	32.3
SLR (in)	14.9
RC (in)	97.3
Rim Rec	5.50 F SDC
Rim Alt	6.00 G
ECE	E11-106R-005309

## Load Capacity (US)

mph / psi	75
40 LS	2680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..