



IS standard



GROWING TOGETHER

# TR 459



PRODUCT DATA SHEET



Bias



# TR 459

🇬🇧 TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

## Performance



Stability



Traction

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 20"	400/70 - 20	TL	-	149 A8	IND	404	1090	-	-	13	12 SDC ; 13 SDC ; 14
Ø 24"	14.9 - 24	TL	8	137 A8	IND	390	1244	562	3657	DW 13	DW 12 ; DW 11 ; DW 13 L
	14.9 - 24	TL	12	145 A8	IND	390	1244	562	3657	DW 13	DW 12 ; DW 11 ; DW 13 L
	16.9 - 24	TL	8	142 A8	IND	450	1310	596	3840	DW 15 L	DW 14 L
	16.9 - 24	TL	10	145 A8	IND	450	1310	590	3850	DW 15 L	DW 14 L
	16.9 - 24	TL	12	149 A8	IND	450	1310	590	3850	DW 15 L	DW 14 L
	17.5 L - 24	TL	8	139 A8	IND	445	1270	557	3825	DW 15 L	DW 14 L
	17.5 L - 24	TL	10	144 A8	IND	445	1270	557	3825	DW 15 L	DW 14 L
	17.5 L - 24	TL	12	148 A8	IND	445	1270	557	3825	DW 15 L	DW 14 L
	18.4 - 24	TL	12	155 A8	IND	472	1375	610	4114	DW 16 L	DW 15 L
	19.5 L - 24	TL	10	147 A8	IND	490	1333	585	4031	DW 16 L	-
	19.5 L - 24	TL	12	151 A8	IND	490	1333	585	4031	DW 16 L	-
	19.5 L - 24	TL	12	151 A8	IND SPL	490	1333	585	4031	DW 16 L	-
	21 L - 24	TL	14	157 A8	IND	533	1378	605	3995	DW 18 L	-
21 L - 24	TL	12	155 A8	IND	533	1378	605	3995	DW 18 L	-	

IND: Industrial - IND SPL: Industrial Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Stability



Traction



	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 26"	18.4 - 26	TL	12	156 A8	IND	472	1425	628	4346	DW 16 L	DW 15 L
	18.4 - 26	TL	14	159 A8	IND	472	1425	628	4346	DW 16 L	DW 15 L
	18.4 - 26	TL	16	162 A8	IND	472	1425	628	4346	DW 16 L	DW 15 L
Ø 28"	16.9 - 28	TL	8	145 A8	IND	440	1410	640	4145	DW 15 L	DW 14 L
	16.9 - 28	TL	10	148 A8	IND	440	1410	640	4145	DW 15 L	DW 14 L
	16.9 - 28	TL	12	152 A8	IND	445	1410	640	4272	DW 15 L	DW 14 L
	18.4 - 28	TL	12	157 A8	IND	472	1475	664	4495	DW 16 L	DW 15 L
	21 L - 28	TL	12	157 A8	IND	535	1480	-	-	DW 18 A	-
Ø 30"	16.9 - 30	TL	12	153 A8	IND	440	1470	657	4484	DW 15 L	DW 14 L

IND: Industrial



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference