



GIANT TRAX

Description

GIANT TRAX has been designed for skid steer loaders in scrap yard operations, on rough concrete surfaces, recycling applications and mines. The extra deep tread with wider and sturdier blocks provides best traction, stability, and puncture resistance. The special tread compound results in exceptional cut and chip resistance along with excellent wear resistance on all types of terrains.

UM

US Standard

Construction

◆ Bias

Machinery

Industrial & Construction ■ Skid Steer



Version STANDARD

Tire Type TL

Tyre size 14-17.5

LI/SS

Dimensions US Standard

| | |
|---------------|-----------------|
| USA Code | 94064403 |
| SW (US) (in) | 13.8 |
| OD (US) (in) | 36.0 |
| SLR (US) (in) | 16.6 |
| RC (US) (in) | 106.9 |
| Rim Rec | 10.50 |
| ECE | E11-106R-006019 |

Load Capacity (US)

| mph / psi | 80 |
|-----------|------|
| 5 | 8540 |
| 10 | 6750 |
| 15 | 6240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..