



IS standard



GROWING TOGETHER

EM 937 IND3 (ECH)



PRODUCT DATA SHEET



Bias



EM 937 IND3 (ECH)

EM 937 (E-3) IND is specially designed for empty-container-handling operations in stacking and loading applications. It features excellent durability and a long tire life. EM 937 (E-3) IND is ideal on paved surfaces and for all operations requiring a high level of handling in the port. *For size 14.00-24 please confirm service rim or consult manufacturer/distributor.

Technologies



Heavy Duty

Performance



Cut and Chip Resistance



Durability



Handling and Comfort



Hard Surfaces



Stability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	14.00 - 24	TT	28	-	PORT IND	375	1368	628	4050	10.00 W	-
	14.00 - 24	TL	28	-	PORT IND	375	1368	628	4050	10.00 W	-
	14.00 - 24	TL	28	-	PORT IND	375	1368	628	4050	10.00 WA	10.00 VA
	14.00 - 24	TT	32	-	PORT IND	375	1368	628	4050	10.00 W	-
NEWSIZE											

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference