



## EARTHMAX SR 46

### Description

EARTHMAX SR 46 for rigid haul trucks is BKT's innovative response to severe rocky, abrasive and harsh mining environments. This tire has been specifically designed to carry heavy loads offering superior resistance to cuts and chips as well as a long tire life-cycle. The All Steel casing and belts provide extraordinary protection against shocks, fatigue and flats to maximize uptime and enhance productivity.



### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Rigid Dump Truck

|           |                         |
|-----------|-------------------------|
| Version   | HEAT RESISTANT COMPOUND |
| Tire Type | TL                      |
| Tyre size | 30.00R51                |
| LI/SS     | 230;B                   |

## Dimensions IS Standard

|               |           |
|---------------|-----------|
| OD (IS) (mm)  | 2895      |
| SLR (IS) (mm) | 1300      |
| RC (IS) (mm)  | 8800      |
| Rim Rec       | 22.00/4.5 |
| TRA Code      | E4        |

## Load Capacity (IS)

| km/h / bar | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 25750 | 26500 | 28000 | 29000 | 30000 | 30750 | 31500 | 32500 | 33500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..