



US standard



GROWING TOGETHER

ROCK GRIP IND4 (ECH)



PRODUCT DATA SHEET



Bias



ROCK GRIP IND4 (ECH)

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) is a bias-ply tire designed for Empty container handler in several applications including industrial handling and steelworks. The special ROCK GRIP compound ensure particular heat resistance along with great stability and durability.

Technologies



Special Compound

Performance



Durability



Heat Resistance



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 24"	94046287	12.00 - 24	TT	20	-	PORT IND	49.8	12.4	23.4	147.8	42	224	8.5	8.0
	94047413	12.00 - 24	TT	24	-	PORT IND	49.8	12.4	23.4	147.8	42	237	8.5	8.0
	94031139	14.00 - 24	TL	24	-	PORT IND	55.5	14.8	25.5	164.3	64	392	10.00 W	-
	94030743	14.00 - 24	TL	28	-	PORT IND	55.5	14.8	25.5	164.3	64	392	10.00 W	-
	94049752	14.00 - 24	TL	28	-	PORT IND	55.5	14.8	25.5	164.3	64	397	10.00 WA	10.00 VA
	94030590	14.00 - 24	TL	32	-	PORT IND	55.5	14.8	25.5	164.3	64	413	10.00 W	-
	94059201	14.00 - 24	TL	32	-	PORT IND	55.5	14.8	25.5	164.3	64	416	10.00 WA	10.00 VA
Ø 25"	94052059	16.00 - 25	TL	32	-	PORT IND	60.0	18.5	27.5	177.7	65	592	11.25/2.0	13.00/2.0
	94060412	16.00 - 25	TL	36	-	PORT IND	60.0	18.5	27.5	177.7	65	617	11.25/2.0	13.00/2.0

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference