



## TR 126

### Description

TR 126 is designed to fit small tractors in soil tillage operations. The deep lugs and the tread pattern provide excellent traction and outstanding load capacity features providing best tire performance in all operating conditions.

### UM

US Standard

### Construction

⊠ Bias

### Machinery

Agriculture ▪ Small Tractor



Version	STANDARD
Tire Type	TL
Tyre size	6-14
LI/SS	63;A8

## Dimensions US Standard

USA Code	94053513
SW (US) (in)	6.2
OD (US) (in)	25.8
SLR (US) (in)	12.0
RC (US) (in)	77.9
Rim Rec	5 JA; 5 KB
ECE	E11-106R-003476
TRA Code	R1

## Load Capacity (US)

mph / psi	28
25	600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..