



IS standard



GROWING TOGETHER

FL 252



PRODUCT DATA SHEET



Bias



FL 252

FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

Performance



Cut and Chip Resistance



Durability



Stability

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 8"	5.00 - 8	TT	8	-	STD	138	480	-	-	3.00 D	3.25 I
	5.00 - 8	TT	10	-	STD	138	480	-	-	3.00 D	3.25 I
Ø 9"	6.00 - 9	TT	10	-	STD	170	550	-	-	4.00 E	-
Ø 10"	6.50 - 10	TT	10	-	STD	185	605	-	-	5.00 F	5.50 F
Ø 12"	7.00 - 12	TT	14	-	STD	192	683	-	-	5.00 S	-
Ø 15"	8.15 - 15 (28 X 9 - 15)	TT	14	-	STD	220	720	-	-	7.00	7 BD
	8.25 - 15	TT	14	-	STD	240	855	-	-	6.50	7.0

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference