



IS standard



GROWING TOGETHER

AIROMAX

RADIAL CRANE TIRES

AM 27



PRODUCT DATA SHEET



Radial



AIROMAX AM 27
RADIAL CRANE TIRES

UK AIROMAX AM 27 is the ideal road-oriented tire for construction applications with cranes. It features extraordinary heat resistance and outstanding riding comfort. AIROMAX AM 27 is a high-speed tire particularly suitable for all operations requiring a high level of handling.

Technologies



High Speed



All Steel

Performance



High Load Capacity



Handling and Comfort



Heat Resistance

	Tire size	Type	STAR RATING	LI/SS	Version	O.W.	O.D.	SLR	RC	RIM	
						(mm)	(mm)	(mm)	(mm)	Rec.	Alt.
Ø 24"	385/95 R 24 (14.00 R 24)	TT	-	170 F	STD	372	1363	626	4175	10.00 W	-
Ø 25"	385/95 R 25 (14.00 R 25)	TL	-	170 F	STD	372	1363	626	4175	10.00/1.5	-
	445/80 R 25 (17.5 R 25)	TL	-	170 F	STD	440	1350	629	4115	14.00/1.5	14.00/1.3
	NEWSIZE										
	445/95 R 25 (16.00 R 25)	TL	-	174 F	STD	440	1490	695	4587	11.25/2.0	11.00/1.7 CR ; 11.00/1.7 CRL
	505/95 R 25 (18.00 R 25)	TL	-	186 E	STD	492	1600	728	4900	13.00/2.5	-
	525/80 R 25 (20.5 R 25)	TL	-	176 F	STD	530	1481	681	4534	17.00/2.0	17.00/1.7 CR

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice.