



IS standard



GROWING TOGETHER

AW 711



PRODUCT DATA SHEET



Radial



167



AW 711

AW 711 is a radial implement tire specially designed for modern farming, and suitable for haulage, hay harvesting and soil tillage applications. Thanks to its special tread compound, AW 711 has an extended product life-cycle, whether it is used on soft or hard surfaces. The low rolling resistance during on-road travel ensures significant savings in fuel consumption. Thanks to the VF technology, AW 711 can carry heavy loads at low inflating pressure.

Technologies



Steel Belted

Performance



Durability



Fuel Economy



High Load Capacity



Stubble Resistance

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 16.5"	265/70 R 16.5	134 A8/B	8.25	-	264	773	343	2286	370	SR
	305/70 R 16.5	148 A8/B	9.75	-	325	851	371	2552	410	SR
	340/60 R 16.5	145 A8/B	11	-	324	820	368	2476	390	SR
	380/55 R 16.5	150 A8/B	12	11.75	360	830	372	2500	390	SR
	395/55 R 16.5	152 A8/B	12	-	394	838	365	2516	400	SR
	VF 410/50 R 16.5	153 B	AG 11.75	-	410	835	350	2513	400	SB
Ø 17"	VF 480/45 R 17	167 A8/B	16.00	-	491	866	363	2644	410	SB
Ø 18"	IF 340/65 R 18	153 A8/B	W 11	-	330	899	381	2703	450	SR
	400/60 R 18	159 A8/B	14	13	394	945	419	2807	450	SR
	440/55 R 18	159 A8/B	14	13	410	945	432	2893	450	SR
Ø 19.5"	15 R 19.5	139 D	11.75	12.75	389	1019	471	3094	475	SR
	380/70 R 19.5	159 A8/B	12.15	13.15	389	1019	444	3038	475	SR

SR: Stubble Resistant - SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index