



## AGRIMAX RT 765



### Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	SPECIAL
Tire Type	TL
Tyre size	320/70R24
LI/SS	116;D

## Dimensions IS Standard

SW (mm)	319
OD (mm)	1094
SLR (mm)	502
RC (mm)	3245
Rim Rec	W 10
Rim Alt	W 9; W 11
ECE	E11-106R-005827
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	690	800	915	1025	1140	1250
50	725	845	960	1080	1200	1315
40	755	880	1005	1125	1250	1370
30	795	925	1055	1185	1315	1440
10 LT	925	1075	1225	1375	1525	1675
10 HT	795	925	1055	1185	1315	1440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..