



US standard



GROWING TOGETHER

# ROCK GRIP (L-4)



PRODUCT DATA SHEET



Bias



# ROCK GRIP (L-4)

ROCK GRIP (L-4) is a bias-ply tire designed for wheel loader operations in severe loading service and on rough ground conditions. Its specially designed, cut-and-chip-resistant tread compound minimizes punctures thereby reducing machine downtime. The (L-4) tread depth provides an extended tire life-cycle.

### Technologies



Deep Tread

### Performance



Cut and Chip Resistance



Heavy Duty



High Puncture Resistance



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 25"	94031214	14.00 - 25	TT	24	-	STD	55.5	14.8	25.6	164.3	64	391	10.00/1.5	-
	94031146	14.00 - 25	TL	24	-	STD	55.5	14.8	25.6	164.3	64	397	10.00/1.5	-
	94031221	14.00 - 25	TT	28	-	STD	55.5	14.8	25.6	164.3	64	396	10.00/1.5	-
	94031153	14.00 - 25	TL	28	-	STD	55.5	14.8	25.6	164.3	64	401	10.00/1.5	-
	94031160	14.00 - 25	TL	32	-	STD	55.5	14.8	25.6	164.3	64	420	10.00/1.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference