



US standard



GROWING TOGETHER

AGRIMAX SPARGO
RADIAL 'V' SPRAYER TIRES

SB



PRODUCT DATA SHEET



Radial



176

Technologies



VF Technology



Steel Belted



Strong Casing



Larger Footprint



High Speed

Performance



On/Off Road



Self-Cleaning



Handling and Comfort



Stability



AGRIMAX SPARGO SB

RADIAL VF SPRAYER TIRES

AGRIMAX SPARGO SB is a special row crop tire that is particularly suitable for tractors and sprayers in open-field spraying and row crop applications, or for specialized tractors in orchards and vineyards. Thanks to its advanced VF-technology (Very Increased Flexion), the tire is able to carry 40% heavier load compared to a standard tire of the same size at the same inflation pressure. The wide footprint ensures uniform weight distribution as well as low soil compaction in the fields. AGRIMAX SPARGO SB stands for excellent performance and high speed-efficiency both on and off the road, up to 65 km/h. Moreover, the robust polyester casing provides improved durability, better handling and dimensional stability as well as enhanced equipment stability and control both in the fields and on the road, thus avoiding the risk of tire slippage and reducing fuel consumption. AGRIMAX SPARGO SB features a special sidewall design that provides tire flexibility and reduces vibrations - essential for operations with precision sprayers. Finally, the steel-belted construction guarantees excellent puncture resistance plus outstanding support of heavy loads, while the extraordinarily strong lug design stands for improved traction. The combination of all these features results in a lower economic and environmental impact, increasing productivity and operator comfort at the same time.

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 32"	94076352	VF 270/95 R 32	148 D	W 9	-	11.0	52.7	24.3	160.6	44	143	SB
Ø 34"	94513598	VF 420/85 R 34 NEW SIZE	165 D	DW 15 L	DW 14 L	16.9	62.1	28.2	188.1	60	313	SB
Ø 36"	94511594	VF 270/95 R 36	150 D	W 9	-	11.0	56.7	26.1	173.1	44	158	SB
Ø 38"	94506309	VF 270/95 R 38	151 D	W 9	-	11.0	58.7	27.2	179.0	44	166	SB
	94513833	VF 380/95 R 38 NEW SIZE	165 D	W 13	W 12	15.6	66.5	30.2	201.4	60	323	SB
Ø 46"	94076123	VF 380/90 R 46 CFO	173 D	W 13	W 12 ; DW 13	15.7	72.9	33.7	223.1	55	360	SB
Ø 48"	94076499	VF 270/95 R 48	155 D	W 9	-	11.0	68.7	32.1	211.5	44	201	SB
Ø 50"	94076116	VF 380/90 R 50 CFO	175 D	W 13	W 12 ; DW 13	15.7	76.9	35.6	235.7	55	397	SB
Ø 54"	94512898	VF 270/95 R 54	157 D	W 9	-	11.0	74.8	35.2	230.0	44	227	SB
	94513284	VF 320/90 R 54	168 D	W 11	W 10 ; DW 10 A ; DW 11	12.7	77.2	36.1	237.4	52	312	SB
	94513260	VF 380/90 R 54	176 D	W 13	W 12 ; DW 12 ; W 13 A ; DW 13 ; DW 13 A	15.6	81.1	37.7	248.4	55	-	SB

SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference