



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 402



PRODUCT DATA SHEET

EARTHMAX SR 402
RADIAL OTR TIRES



EARTHMAX SR 402 (E-4) is an *All Steel* radial tire specifically engineered for long-haul dump trucks in mines and quarries. The unique tread design ensures reduced heat buildup and provides excellent traction and stability on all types of terrains and tracks where particular equipment control is a main requirement. The symmetrical, E-4-deep rock tread ensures easy fitment as well as excellent self-cleaning properties even in muddy conditions. The *All Steel* casing along with the specifically developed tread compound provide excellent wear and extraordinary resistance against cuts and punctures in addition to high load capacity and great durability. As a result, EARTHMAX SR 402 (E-4) reduces machinery downtime and is particularly suitable for long hauls even at full load.



Radial



Technologies



All Steel



Heavy Duty

Performance



Traction



Stability



For muddy ground



Cut and Chip Resistance



Durability



Handling and Comfort

Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 25"	14.00 R 25	TL	E-4	***	171 B	CRC	118	375	1385	644	4261	35	10.00/2.0	-
	NEWSIZE													
	16.00 R 25	TL	E-4	***	183 B	CRC	131	450	1520	694	4640	44	11.25/2.0	-
16.00 R 25	TL	E-4	***	183 B	STDC	158	450	1520	694	4640	44	11.25/2.0	-	

CRC: Cut Resistance Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference