



AGRIMAX RT 855



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	480/80R38
LI/SS	149;A8/B

Dimensions US Standard

USA Code	94045341
SW (US) (in)	18.7
OD (US) (in)	68.8
SLR (US) (in)	30.9
RC (US) (in)	203.2
Rim Rec	DW 16 L
Rim Alt	W 14 L; W 15 L
ECE	E4-106R-001822
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23
30	3950	4590	5240	5870	6530	7160
25	3950	4590	5240	5870	6530	7160
20	4220	4920	5610	6290	6990	7670
5 LT	5290	6150	7010	7880	8740	9600
5 HT	4220	4920	5610	6290	6990	7670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..