



US standard



GROWING TOGETHER

# FL 630 ULTRA



PRODUCT DATA SHEET



Radial



# FL 630 ULTRA

FL 630 ULTRA is suitable for trailers, tankers and spreaders. Thanks to its reinforced bead and the particular tread design, it is the ideal tire for multipurpose use on any kind of land or on the road. FL 630 ULTRA stands for extraordinarily reduced soil compaction.

### Technologies



Reinforced Bead

### Performance



Reduced Soil Compaction

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 22.5"	94046065	500/60 R 22.5	155 D/ 166 A8	AG 16.00	15.00 ; 16.00 ; 17.00	19.8	46.1	20.5	141.4	36	217	STD
	94052790	560/45 R 22.5	152 D/ 163 A8	AG 16.00	-	21.4	42.4	19.3	129.5	36	203	STD
	94052509	560/60 R 22.5	161 D/ 172 A8	AG 16.00	16.00 ; 17.00 ; AG 20.00	21.4	49.0	21.1	148.0	36	248	STD
	94054220	600/50 R 22.5	159 D/ 170 A8	AG 20.00	-	24.1	46.1	20.4	139.1	38	247	STD
	94052905	710/40 R 22.5	161 D/ 172 A8	AG 24.00	-	28.6	44.9	20.2	137.4	31	278	STD
Ø 26.5"	94044955	600/55 R 26.5	165 D/ 176 A8	AG 20.00	-	24.1	52.5	22.8	160.2	38	299	STD
	94044269	650/55 R 26.5	169 D/ 180 A8	AG 20.00	-	25.4	54.7	23.6	165.6	38	321	STD
	94047284	710/50 R 26.5	170 D/ 181 A8	AG 24.00	AG 20.00	28.6	54.4	23.6	165.7	38	352	STD
	94054831	800/45 R 26.5	174 D/ 184 A8	AG 28.00	AG 24.00	32.6	54.8	24.3	166.9	40	413	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference