



## LOADER SPECIAL



### Description

LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.

### UM

IS Standard

### Construction

◆ Bias

### Machinery

OTR ■ Dozer

Version	STANDARD
Tire Type	TL
Tyre size	26.5-25
LI/SS	

## Dimensions IS Standard

OD (IS) (mm)	1815
SLR (IS) (mm)	833
RC (IS) (mm)	5372
Rim Rec	22.00/3.0
TRA Code	L5

## Load Capacity (IS)

km/h / bar	5.50
10	17000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..