



## AGRIMAXFACTOR

### Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors perfect for haulage and soil tillage operations. The improved tread design with increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance. AGRIMAXFACTOR's overall advantages are great handling in combination with driving comfort and excellent durability. The exclusive sidewall shows the "E-READY" logo that highlights BKT's commitment to electric mobility.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	480/70R34
LI/SS	155;D

## Dimensions IS Standard

SW (IS) (mm)	479
OD (IS) (mm)	1580
SLR (IS) (mm)	729
RC (IS) (mm)	4761
Rim Rec	W 15 L
Rim Alt	W 14 L; W 16 L
ECE	E11-106R-007643
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
65	1515	1785	2055	2290	2560	2790	3065	3295	3605	3875
50	1590	1875	2160	2405	2690	2935	3220	3460	3790	4070
40	1660	1955	2250	2505	2805	3060	3355	3610	3950	4245
30	1740	2055	2365	2635	2945	3215	3525	3795	4150	4460
10 LT	2030	2390	2755	3070	3430	3745	4105	4420	4835	5195
10 HT	1740	2055	2365	2635	2945	3215	3525	3795	4150	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..