



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 34



PRODUCT DATA SHEET



Radial



**EARTHMAX SR 34**  
RADIAL OTR TIRES

EARTHMAX SR 34 is an All Steel radial tyre specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. EARTHMAX SR 34 is ideal for handling heavy loads. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under the most heavy-duty service conditions.

**Technologies**



All Steel



Block Pattern



Heavy Duty



Reinforced Bead

**Performance**



Cut and Chip Resistance



Durability



Stability



Traction

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
<b>Ø 25"</b>	16.00 R 25	TL	E-3+	**	177 B	CRC	190	440	1508	693	4575	36	11.25/2.0	-
	16.00 R 25	TL	E-3+	***	183 B	CRC	190	440	1508	693	4575	36	11.25/2.0	-
	16.00 R 25	TL	E-3+	***	183 B	UCRC	-	440	1508	693	4575	36	11.25/2.0	-

CRC: Cut Resistant Compound - UCRC: Ultra Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference