



RIDEMAX FL 693 M



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tanker

Version	STANDARD
Tire Type	TL
Tyre size	580/65R22.5
LI/SS	166;D

Dimensions US Standard

USA Code	94037254
SW (US) (in)	22.7
OD (US) (in)	52.2
SLR (US) (in)	22.5
RC (US) (in)	158.7
Rim Rec	AG 18.00
Rim Alt	AG 16.00; AG 17.00; AG 20.00
ECE	E4-106R-000804

Load Capacity (US)

mph / psi	15	17	23	29	35	41	46	52	58
45	3980	4520	5380	6350	7260	8070	9030	9890	10750
40	4330	4920	5840	6900	7890	8760	9820	10760	11680
30	5240	5940	7080	8340	9560	10610	11880	13020	14140
25	5890	6680	7950	9380	10740	11930	13360	14630	15890
15	6830	7760	9240	10900	12470	13860	15510	16990	18460
5	7790	8840	10520	12410	14200	15770	17670	19360	21030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..