



AGRIMAX SPARGO


Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TL
Tyre size	VF480/80R50
LI/SS	179;D

Dimensions IS Standard

SW (IS) (mm)	479
OD (IS) (mm)	2038
SLR (IS) (mm)	947
RC (IS) (mm)	6224
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-004757-01
TRA Code	R1

Load Capacity (IS)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
70	3945	4370	4790	5005	5285	5425	5565	5850	6130	6345	6625	6835	7050
From 65 to 40	4340	4805	5270	5500	5810	5965	6120	6430	6740	6975	7285	7515	7750
30	4425	4900	5375	5610	5925	6085	6240	6560	6875	7110	7430	7665	7905
20	4510	4995	5480	5720	6045	6205	6365	6685	7010	7250	7575	7815	8060
10	4770	5285	5795	6050	6390	6560	6730	7075	7415	7670	8010	8265	8525

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..