



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ▪ Sprayer

Version	SPECIAL
Tire Type	TL
Tyre size	VF580/85R46CFO
LI/SS	179;D

Dimensions US Standard

USA Code	94516148
SW (US) (in)	23.8
OD (US) (in)	84.9
SLR (US) (in)	37.3
RC (US) (in)	254.0
Rim Rec	DW 20 B
Rim Alt	DW 21 B, DW18L
ECE	E11-106R-0011691
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29
45	7780	9030	10270	11670	12920	14160	15550
from 40 to 25	8540	9910	11280	12820	14190	15550	17080
20	8720	10110	11510	13070	14470	15860	17430
12	8880	10310	11730	13330	14750	16170	17770
5	9400	10900	12410	14100	15610	17110	18790
5 HT	8720	10110	11510	13070	14470	15860	17430
Upto 5 Cyc	12690	14730	16750	19040	21060	23090	25370
Upto 10 Cyc	11580	13440	15290	17370	19220	21080	23160
Upto 20 Cyc	9700	11250	12810	14550	16100	17660	19400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..