



IS standard



GROWING TOGETHER

ROCK GRIP IND4 (RS)



PRODUCT DATA SHEET



Bias



ROCK GRIP IND4 (RS)

ROCK GRIP IND4 (RS) is a bias-ply tire designed for reach stackers in several applications including industrial handling and steelworks. In airport hubs ROCK GRIP IND4 (RS) can be employed also for push back tractors. The special ROCK GRIP compound ensures particular heat resistance along with great stability and durability.

Technologies



Special Compound

Performance



Durability



Heat Resistance



Stability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 25"	18.00 - 25	TL	40	-	PORT IND	510	1650	753	4885	13.00/2.5	15.00/2.5
Ø 33"	18.00 - 33	TL	36	-	PORT IND	510	1887	869	5586	13.00/2.5	-
	18.00 - 33	TL	40	-	PORT IND	510	1887	869	5586	13.00/2.5	-
	18.00 - 33	TL	44	-	PORT IND	510	1887	869	5586	13.00/2.5	-

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference