



US standard



GROWING TOGETHER

MAGLIFT CUSHION



PRODUCT DATA SHEET



Solid



MAGLIFT CUSHION

MAGLIFT CUSHION is a solid tire specially designed for forklifts in industrial and logistics applications. The tire features a robust tread pattern that provides excellent front and lateral traction along with top steering control and low rolling resistance. The reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim. The tread is made of a highly cut-and-chip resistant compound resulting in an extended tire life-cycle. The unique sidewall design with apertures ensures a cushioning effect that enables the tire to absorb and dampen vibrations and impacts. This helps to reduce the amount of shock and vibration that is transmitted to the equipment and operator, improving ride comfort and reducing the risk of damage to the equipment.

Technologies



Reinforced Bead

Performance



Traction



Steering Control



Low Rolling Resistance



Cut and Chip Resistance



Durability

| | US CODE | Tire size | Type | PR | LI/SS | Version | O.D. (In.) | S.W. (In.) | SLR (In.) | RC (In.) | TREAD DEPTH (32nds) | TIRE WEIGHT (lbs) | RIM | |
|-------|----------|---|------|----|-------|---------|---------------|---------------|--------------|-------------|------------------------|----------------------|-------------|------|
| | | | | | | | | | | | | | Rec. | Alt. |
| Ø 9" | 94515486 | 6.00 - 9 | - | - | - | STD | 20.8 | 5.4 | - | - | 57 | 52 | 4.00 E - 9 | - |
| | | NEWSIZE | | | | | | | | | | | | |
| Ø 10" | 94515509 | 6.50 - 10 | - | - | - | STD | 22.6 | 6.1 | - | - | 64 | 70 | 5.00 F - 10 | - |
| | | NEWSIZE | | | | | | | | | | | | |
| Ø 12" | 94075928 | 7.00 - 12 | - | - | - | STD | 25.9 | 6.4 | - | - | 68 | 93 | 5.00 S - 12 | - |
| Ø 15" | 94515523 | 8.15 - 15 / 28 X 9 - 15 (225/75 - 15) | - | - | - | STD | 27.2 | 8.3 | - | - | 63 | 119 | 7.00 - 15 | - |
| | | NEWSIZE | | | | | | | | | | | | |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference