



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 468



PRODUCT DATA SHEET



Radial

E-4

B

257



# EARTHMAX SR 468

RADIAL OTR TIRES

🇬🇧 EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensure effective heat dissipation. Also, the sturdy square shoulder assist in ejecting loose stones to protect the tire from injury. EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.

### Technologies



All Steel



Strong Casing

### Performance



Hard Rocky Surface



High Load Capacity



Durability



Self-Cleaning

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 49"	27.00 R 49	TL	E-4	**	223 B	CRC	392	735	2720	1235	8351	83	19.50/4.0	-
	27.00 R 49	TL	E-4	***	226 B	CRC	432	735	2720	1235	8351	83	19.50/4.0	-
	27.00 R 49	TL	E-4	**	223 B	STDC	458	735	2720	1235	8351	83	19.50/4.0	-
	27.00 R 49	TL	E-4	***	226 B	STDC	505	735	2720	1235	8351	83	19.50/4.0	-
Ø 57"	37.00 R 57	TL	E-4	**	245 B	CRC	725	1030	3425	1520	10315	88	27.00/6.0	29.00/6.0
	37.00 R 57	TL	E-4	**	245 B	STDC	850	1030	3425	1520	10315	88	27.00/6.0	29.00/6.0
	37.00 R 57	TL	E-4	**	245 B	HRC	1020	1030	3425	1520	10315	88	27.00/6.0	29.00/6.0
	37.00 R 57	TL	E-4	***	249 B	HRC	1100	1030	3425	1520	10315	88	27.00/6.0	29.00/6.0
	40.00 R 57	TL	E-4	**	250 B	CRC	800	1125	3575	1595	10700	100	29.00/6.0	32.00/6.0
	40.00 R 57	TL	E-4	**	250 B	STDC	950	1125	3575	1595	10700	100	29.00/6.0	32.00/6.0
	40.00 R 57	TL	E-4	**	250 B	HRC	1130	1125	3575	1595	10700	100	29.00/6.0	32.00/6.0
	46/90 R 57	TL	E-4	**	252 B	CRC	825	1140	3575	1590	10800	100	29.00/6.0	32.00/6.0
	46/90 R 57	TL	E-4	**	252 B	STDC	980	1140	3575	1590	10800	100	29.00/6.0	32.00/6.0
	46/90 R 57	TL	E-4	**	252 B	HRC	1165	1140	3575	1590	10800	100	29.00/6.0	32.00/6.0
	50/80 R 57	TL	E-4	**	257 B	CRC	950	1205	3610	1597	10870	96	32.00/6.0	34.00/6.0 ; 29.00/6.0

CRC: Cut Resistance Compound - HRC: Heat Resistant Compound - STDC: Standard Compound

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial

E-4

B

257

Technologies



All Steel



Strong Casing

Performance



Hard Rocky Surface



High Load Capacity



Durability



Self-Cleaning



	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 57"	50/80 R 57	TL	E-4	**	257 B	STDC	1130	1205	3610	1597	10870	96	32.00/6.0	34.00/6.0 ; 29.00/6.0
	50/80 R 57	TL	E-4	**	257 B	HRC	1340	1205	3610	1597	10870	96	32.00/6.0	34.00/6.0 ; 29.00/6.0

STDC: Standard Compound - HRC: Heat Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference