



BK-LOADER 53

Description

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.



UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Loader

Version ARAMID BELTED

Tire Type TL

Tyre size 405/70R20

LI/SS 155A2/151A4;

Dimensions IS Standard

SW (IS) (mm)	407
OD (IS) (mm)	1097
SLR (IS) (mm)	511
RC (IS) (mm)	3339
Rim Rec	13
Rim Alt	14; 13 SDC; 12;12 SDC

Load Capacity (IS)

km/h / bar	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
20 TRANSPORT	1210	1520	1805	2090	2375	2640	2905	3170	3450
10 LOADING	1375	1725	2050	2375	2700	3000	3300	3600	3875
Static	2200	2750	3275	3800	4325	4800	5300	5750	6200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..