



MULTIMAX MP 529



MULTIMAX MP 529 is a steel belted multi-purpose radial tire designed for telehandlers in industrial applications. Its tread design has been specially developed for hard surfaces. The strong sidewall and the larger footprint area ensure outstanding stability in lift mode. MULTIMAX MP 529 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

IS Standard

 Radial

Промышленность ▪ Телескопический погрузчик

Version	STEEL BELTED
---------	--------------

Tire Type	TL
-----------	----

	340/80R18
--	-----------

	143;A8/B
--	----------

undefined IS Standard

SW (mm)	343
OD (mm)	1001
SLR (mm)	445
RC (mm)	3007
Rim Rec	11; 11 SDC; W 11
Rim Alt	W 10; 12; 12 SDC
ECE	E11-106R-002972

Load Capacity (IS)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 Cyc.	1600	1965	2315	2660	3030	3295	3725	3930	4090
Static	2450	3010	3545	4080	4640	5050	5710	6020	6270

24-03-2026