



IS standard



GROWING TOGETHER

# RIB F3



PRODUCT DATA SHEET



Bias



Technologies



Hard Compound

Performance



Durability



Steering Control



Stubble Resistance



# RIB F3

RIB F3 is a field-oriented tire designed for 2WD tractors in soil tillage and haulage operations. Some sizes are suitable for transport applications using trailers. The RIB F3 tire is the ideal partner for all operations that require a high level of handling. It has been designed with a hard compound to ensure great durability and stubble resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	9.00 - 16	W 8	6.00 F; W 7;W 8 L	245	878	387	2573	HD	12	TT	120 A6/ 112 A8
	9.00 - 16	W 8	6.00 F; W 7;W 8 L	245	878	387	2573	STD	12	TT	120 A6/ 112 A8
	9.00 - 16	W 8	6.00 F; W 7;W 8 L	245	878	387	2573	STD	12	TL	120 A6/ 112 A8

HD: Heavy Duty - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference