



IS standard



GROWING TOGETHER

BK 823



PRODUCT DATA SHEET



Bias



127

Technologies



Block Pattern

Performance



Cut and Chip Resistance



Heavy Duty



Steering Control



BK 823

🇬🇧 BK 823 is a tire designed for tractors, implement and trailers mainly in soil tillage and haulage applications both in the fields and on the road. Its special block pattern makes the tire particularly suitable for heavy-duty service where excellent steering performance is required. An HD version is also available with improved cut and chip resistance.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	9.00 - 16	6.5	-	245	891	394	2583	HD	14	TT	127 A8
	9.00 - 16	6.5	-	245	891	394	2583	STD	12	TT	124 A8
	9.00 - 16	6.5	-	245	891	394	2583	STD	14	TT	127 A8
	9.00 - 16	6.5	-	245	891	394	2583	STD	10	TL	121 A8

HD: Heavy Duty - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference