



IS standard



GROWING TOGETHER

XL GRIP (SCRAPER)



PRODUCT DATA SHEET



Bias

E-3



XL GRIP (SCRAPER)



XL GRIP (SCRAPER) is a non-directional wide-base tire, particularly suitable for scrapers on any terrain. The tire features a strong casing and a special tread compound providing high cut and puncture resistance as well as excellent durability and traction even during heavy-duty operations. Additional features are best self-cleaning properties and exceptional stability.

Performance



	Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 29"	29.5 - 29	TL	E-3	28	-	STD	-	760	1965	-	-	39	25.00/3.5	26.00/3.5
	33.25 - 29	TL	E-3	32	-	STD	-	862	2120	-	-	46	27.00/3.5	26.00/3.5
Ø 35"	33.25 - 35	TL	E-3	32	-	STD	-	862	2270	-	-	46	27.00/3.5	29.00/3.5
	33.25 - 35	TL	E-3	38	-	STD	-	862	2270	-	-	46	27.00/3.5	29.00/3.5
	37.25 - 35	TL	E-3	36	-	STD	-	955	2364	-	-	52	31.00/4.0	29.00/3.5
Ø 39"	37.5 - 39	TL	E-3	52	-	STD	-	975	2570	-	-	52	32.00/4.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference