



## MULTIMAX MP 540



### Description

MULTIMAX MP 540 has been designed by BKT for multi-purpose vehicles in municipality/maintenance applications. It is suitable for all universal vehicles. Thanks to the All Steel casing, MULTIMAX MP 540 enables to carry heavy loads at high speeds. In addition, its block pattern design provides outstanding stability and durability.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ▪ Universal Vehicle, Industrial & Construction ▪ Universal Vehicle

Version	STANDARD
Tire Type	TL
Tyre size	275/80R20
LI/SS	134;K

## Dimensions US Standard

USA Code	94071357
OD (US) (in)	37.6
SLR (US) (in)	17.4
RC (US) (in)	114.7
Rim Rec	W9
Rim Alt	9
ECE	E11-54R-0020628

## Load Capacity (US)

mph / psi	75
68	4675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..