



EARTHMAX CRUSHER HAUL



Description

EARTHMAX CRUSHER HAUL is an All Steel radial tire designed for transport applications, both on and off the road, as well as mining operations and quarry applications. It features enhanced durability and mileage along with high load capacity thanks to the strong steel-belted construction and casing. The block-type tread pattern provides excellent traction. In addition, EARTHMAX CRUSHER HAUL ensures excellent riding comfort, less driving fatigue and superior handling

UM

US Standard

Construction

 Radial

Machinery

OTR ■ On/Off Truck

Version STANDARD

Tire Type TT

Tyre size 12.00R24

LI/SS 160/156;K

Dimensions US Standard

USA Code	94075959
OD (US) (in)	48.4
SLR (US) (in)	22.2
RC (US) (in)	149.0
Rim Rec	8.50
Rim Alt	9.00

Load Capacity (US)

mph / psi	125
68 Single	9900
68 Dual	8800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..