



US standard



GROWING TOGETHER

ROCK SPECIAL L-4



PRODUCT DATA SHEET



Bias



ROCK SPECIAL L-4

ROCK SPECIAL (L-4) is a bias-ply tire engineered for loaders operating in severe mining and quarry applications. The extra deep rock pattern delivers excellent traction even under harsh operating conditions, while the wide footprint ensures great stability and operator comfort. ROCK SPECIAL (L-4) features a steel-belted heavy-duty casing and a particularly cut- and-chip-resistant tread compound to provide excellent protection against external damage. The tire stands out for durability and reduced downtime, making it the ideal choice for the toughest requirements in rocky environments.

Technologies



Extra Deep Tread



Reinforced Carcass



Steel Belted

Performance



Cut and Chip Resistance



Cut Resistance



Durability



High Puncture Resistance



Stability



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94517107	26.5 - 25	TL	32	-	SB	-	-	70.3	27.2	-	-	86	1261	22.00/3.0	-
	94517121	29.5 - 25	TL	34	-	SB	-	-	74.0	30.7	-	-	92	1514	25.00/3.5	-

SB: Steel Belted



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference