



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF710/60R30
LI/SS	171;D

Dimensions US Standard

USA Code	94513505
SW (US) (in)	28.3
OD (US) (in)	64.0
SLR (US) (in)	27.6
RC (US) (in)	189.0
Rim Rec	DW 25 B
Rim Alt	DW 24 B; DW 27 B
ECE	E11-106R-0010832
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29
45	6040	7020	8130	9130	10110	11100	12330
from 40 to 25	6640	7730	8940	10030	11110	12200	13560
20	6770	7870	9120	10220	11330	12430	13820
12	6900	8040	9300	10430	11550	12690	14100
5	7300	8500	9830	11030	12220	13410	14910
*Upto 5 Cyc with front loader	9290	10810	12520	14040	15560	17070	18980
5 HT	6770	7870	9120	10220	11330	12430	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..