



US standard



GROWING TOGETHER

AGRIMAX FACTOR



PRODUCT DATA SHEET

AGRIMAXFACTOR



AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent. In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.



Radial



Technologies



E-Ready



High Speed



Heavy Duty

Performance



Durability



Stability



Steering Control



Handling and Comfort

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 24"	94513659	360/70 R 24	122 D/ 125 A8	W 11	W 10 ; W 12	14.1	44.9	20.6	133.3	50	134	STD
		NEWSIZE										
	94071012	380/70 R 24	125 D/ 128 A8	W 12	W 11 ; W 13	15.0	46.9	21.2	138.7	52	148	STD
	94070923	420/70 R 24	130 D/ 133 A8	W 13	W 12 ; W 14 L	16.5	49.1	21.7	143.7	54	178	STD
	94070947	420/70 R 24	134 D/ 137 A8	W 13	W 12 ; W 14 L	16.5	49.1	22.2	145.5	54	178	STD
	94513819	480/70 R 24	138 D/ 141 A8	W 15 L	W 14 L ; W 16 L	19.1	51.6	23.2	153.3	60	228	STD
		NEWSIZE										
Ø 28"	94513673	360/70 R 28	125 D/ 128 A8	W 11	W 10 ; W 12	14.1	49.4	22.7	147.5	50	155	STD
		NEWSIZE										
	94070954	380/70 R 28	127 D/ 130 A8	W 12	W 11 ; W 13	15.0	50.9	23.1	151.0	52	168	STD
	94070633	420/70 R 28	133 D/ 136 A8	W 13	W 12 ; W 14 L	16.5	53.1	23.9	157.5	54	199	STD
	94070718	480/70 R 28	140 D/ 143 A8	W 15 L	W 14 L ; W 16 L	18.9	55.9	25.2	166.9	60	249	STD
	94071135	600/70 R 28	157 D/ 160 A8	DW 20 B	DW 18 L ; W 18 L	24.1	61.1	28.1	183.7	72	385	STD
Ø 30"	94513635	420/70 R 30	134 D/ 137 A8	W 13	W 12 ; W 14 L	16.9	54.8	24.9	163.5	54	210	STD
		NEWSIZE										
	94074792	480/70 R 30	141 D/ 144 A8	W 15 L	W 14 L ; W 16 L	18.9	58.2	26.4	172.9	60	266	STD
	94070152	600/70 R 30	152 D/ 155 A8	DW 20 B	DW 18 L ; W 18 L	24.1	63.1	28.4	187.6	72	384	STD
Ø 34"	94071029	480/70 R 34	149 D/ 152 A8	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.5	186.9	62	292	STD
	94071036	480/70 R 34	155 D/ 158 A8	W 15 L	W 14 L ; W 16 L	18.9	62.2	28.7	187.4	62	310	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference





Radial



Technologies



Performance



Handling and Comfort



	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 38"	94071043	480/70 R 38	145 D/ 148 A8	W 15 L	W 14 L ; W 16 L	18.9	66.2	29.8	196.9	62	318	STD
	94070725	520/70 R 38	150 D/ 153 A8	W 16 L	W 15 L ; W 18 L	20.3	68.9	31.3	206.3	67	370	STD
	94071050	580/70 R 38	155 D/ 158 A8	W 18 L	DW 18 L ; DD 18 L	22.7	71.9	32.4	214.8	72	467	STD
	94076444	620/70 R 38	170 D/ 173 A8	DW 20 B	DW 18 L ; W 18 L	24.6	72.2	33.2	219.7	72	500	STD
	94071142	710/70 R 38	166 D/ 169 A8	DW 23 B	-	28.2	77.1	34.1	228.3	73	629	STD
	94071159	710/70 R 38	171 D/ 174 A8	DW 23 B	DW 25 B	28.2	77.1	34.1	228.3	73	656	STD
	94071166	710/70 R 38	175 D/ 178 A8	DW 23 B	-	28.2	77.1	34.1	228.3	73	656	STD
Ø 42"	94075836	580/70 R 42	158 D/ 161 A8	W 18 L	DW 18 L ; DD 18 L	22.7	74.0	33.7	224.1	72	502	STD
	94073610	620/70 R 42	160 D/ 163 A8	DW 20 B	DW 18 L ; W 18 L	24.6	76.2	34.0	227.8	72	511	STD
	94073627	620/70 R 42	166 D/ 169 A8	DW 20 B	DW 18 L ; W 18 L	24.6	76.2	34.5	228.4	72	532	STD
	94073634	620/70 R 42	173 D/ 176 A8	DW 20 B	DW 18 L ; W 18 L	24.6	76.2	34.5	228.5	72	538	STD
	94070169	710/70 R 42	173 D/ 176 A8	DW 23 B	DW 25 B	28.2	81.1	36.8	244.0	73	710	STD
	94070527	710/70 R 42	176 D/ 179 A8	DW 23 B	DW 25 B	28.2	81.1	36.8	244.0	73	722	STD
Ø 46"	94076451	620/70 R 46	162 D/ 165 A8	DW 20 B	-	24.6	80.2	35.9	239.2	72	580	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. EN-US / 07-2025