



IS standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 41



PRODUCT DATA SHEET

**EARTHMAX SR 41**  
RADIAL OTR TIRES



EARTHMAX SR 41 is an All Steel radial tire perfect for Articulated Dump Trucks, Loaders and Dozers. Thanks to its all steel structure and special block pattern, EARTHMAX SR 41 provides excellent resistance against punctures and an extended service life. In addition to long working hours without downtime, the tire ensures extraordinary comfort. EARTHMAX SR 41 is also available in SH-4\*\*\*\* for Low Profile Dump Trucks (LPDT) used in underground haulage operations.



Radial



**Technologies**



All Steel



Block Pattern

**Performance**



Durability



Traction



Cut Resistance



Comfort

| Ø   | Tire size                                      | Type | TRA CODE | STAR RATING | LI/SS        | Version | TKPH | O.W. | O.D. | SLR  | RC   | TREAD DEPTH (mm) | RIM       |                       |
|-----|--|------|----------|-------------|--------------|---------|------|------|------|------|------|------------------|-----------|-----------------------|
|     |  |      |          |             |              |         |      | (mm) | (mm) | (mm) | (mm) |                  | Rec.      | Alt.                  |
|     |  |      |          |             |              |         |      |      |      |      |      |                  |           |                       |
| 25" | 23.5 R 25                                      | TL   | E-4/L-4  | **/*        | 185 B/195 A2 | CRC     | 161  | 615  | 1611 | 725  | 4790 | 53               | 19.50/2.5 | -                     |
|     | 26.5 R 25                                      | TL   | E-4/L-4  | **/*        | 193 B/202 A2 | CRC     | 185  | 678  | 1742 | 775  | 5150 | 59               | 22.00/3.0 | -                     |
|     | 26.5 R 25                                      | TL   | E-4      | **          | 193 B        | STDC    | 235  | 678  | 1742 | 775  | 5150 | 59               | 22.00/3.0 | -                     |
|     | 26.5 R 25                                      | TL   | SH-4     | ****        | -            | CRC     | -    | 678  | 1742 | 775  | 5150 | 59               | 22.00/3.0 | -                     |
|     | 29.5 R 25                                      | TL   | E-4/L-4  | **/*        | 200 B/208 A2 | CRC     | 225  | 761  | 1861 | 830  | 5510 | 66               | 25.00/3.5 | -                     |
|     | 29.5 R 25 (SW - 772, OD - 1862) <b>NEWSIZE</b> | TL   | E-4/L-4  | **/*        | 200 B/208 A2 | CRC     | 225  | 772  | 1862 | 830  | 5510 | 66               | 25.00/3.5 | -                     |
|     | 29.5 R 25                                      | TL   | E-4      | **          | 200 B        | CRC     | 225  | 761  | 1861 | 830  | 5510 | 66               | 25.00/3.5 | -                     |
|     | 29.5 R 25                                      | TL   | E-4      | **          | 200 B        | STDC    | 285  | 761  | 1861 | 830  | 5510 | 66               | 25.00/3.5 | -                     |
|     | 29.5 R 25                                      | TL   | SH-4     | ****        | -            | CRC     | -    | 761  | 1861 | 830  | 5510 | 66               | 25.00/3.5 | -                     |
|     | 29.5 R 25                                      | TL   | L-4      | ***         | 221 A2       | CRC     | -    | 761  | 1861 | 830  | 5510 | 66               | 25.00/3.5 | -                     |
| 29" | 875/65 R 29 (35/65 R 29)                       | TL   | E-4      | **          | 203 B        | CRC     | 240  | 880  | 1865 | 837  | 5680 | 60               | 27.00/3.5 | 27.00/3.0 ; 28.00/3.5 |
|     | 875/65 R 29 (35/65 R 29)                       | TL   | E-4/L-4  | **/*        | 203 B/214 A2 | CRC     | 240  | 880  | 1865 | 837  | 5680 | 60               | 27.00/3.5 | 27.00/3.0 ; 28.00/3.5 |
|     | 875/65 R 29 (35/65 R 29)                       | TL   | L-4      | *           | 214 A2       | CRC     | -    | 880  | 1865 | 837  | 5680 | 60               | 27.00/3.5 | 27.00/3.0 ; 28.00/3.5 |
|     | 875/65 R 29 (35/65 R 29)                       | TL   | L-4      | **          | 221 A2       | CRC     | -    | 880  | 1865 | 837  | 5680 | 60               | 27.00/3.5 | 27.00/3.0 ; 28.00/3.5 |
| 33" | 35/65 R 33                                     | TL   | SH-4     | ****        | -            | CRC     | -    | 896  | 2063 | 926  | 6283 | 62               | 28.00/3.5 | -                     |

CRC: Cut Resistance Compound - STDC: Standard Compound

**In case of underground mine application, consult your servicing dealer or BKT representative**

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference