



US standard



GROWING TOGETHER

# ROCK GRIP IND4 (RS)



PRODUCT DATA SHEET



Bias



# ROCK GRIP IND4 (RS)

ROCK GRIP IND4 (RS) is a bias-ply tire designed for reach stackers in several applications including industrial handling and steelworks. In airport hubs ROCK GRIP IND4 (RS) can be employed also for push back tractors. The special ROCK GRIP compound ensures particular heat resistance along with great stability and durability.

### Technologies



Special Compound

### Performance



Durability



Heat Resistance



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 25"	94060528	18.00 - 25	TL	40	-	PORT IND	65.0	20.1	29.6	192.3	69	812	13.00/2.5	15.00/2.5
Ø 33"	94046027	18.00 - 33	TL	44	-	PORT IND	74.3	20.1	34.2	219.9	75	999	13.00/2.5	-
	94030224	18.00 - 33	TL	36	-	PORT IND	74.3	20.1	34.2	219.9	75	942	13.00/2.5	-
	94038527	18.00 - 33	TL	40	-	PORT IND	74.3	20.1	34.2	219.9	75	969	13.00/2.5	-

PORT IND: Port Industrial



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference