



## AGRIMAX RT 855



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version SPECIAL

Tire Type TL

Tyre size 380/85R30

LI/SS 135;A8/B

## Dimensions IS Standard

SW (IS) (mm)	380
OD (IS) (mm)	1408
SLR (IS) (mm)	633
RC (IS) (mm)	4190
Rim Rec	W 12
Rim Alt	W 11; W 13
ECE	E4-106R-000594
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1200	1400	1595	1790	1985	2180
40	1200	1400	1595	1790	1985	2180
30	1285	1495	1705	1915	2125	2335
10 LT	1610	1875	2140	2400	2665	2925
10 HT	1285	1495	1705	1915	2125	2335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..