



HARVESTER SPECIAL



Description

HARVESTER SPECIAL has been specifically designed for harvesters. Its dual –angled lugs provide excellent traction in the fields and a comfortable ride on the road. The special tread design provides a large contact area for extraordinary stability. HARVESTER SPECIAL features a strong casing and a particularly cut-and-chip resistant compound ensuring a longer tire life-cycle.

UM

US Standard

Construction

◇◇ Bias

Machinery

Agriculture ■ Harvester

Version	DUAL BEAD
Tire Type	TL
Tyre size	23.1-26
LI/SS	155;A8

Dimensions US Standard

USA Code	94062089
SW (US) (in)	23.1
OD (US) (in)	62.4
SLR (US) (in)	28.3
RC (US) (in)	189.2
Rim Rec	DW 20 B; DW 20 A
TRA Code	R1

Load Capacity (US)

mph / psi	34
25	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..