



SKID MAX SR-SKIDDER



Description

SKID MAX SR-SKIDDER is the new BKT All Steel radial tire specially developed for use in very heavy work environments on hard improved surfaces like road maintenance and waste dump with skid steers, backhoe loaders and telehandlers. Thanks to the strong steel casing and belt construction, this tire provides superior durability and high load carrying capacity.

UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■ Skid Steer

Version	INDUSTRIAL
Tire Type	TL
Tyre size	300/70R16.5
LI/SS	137;A8/B

Dimensions IS Standard

OD (IS) (mm)	830
SLR (IS) (mm)	378
RC (IS) (mm)	2530
Rim Rec	9.75
ECE	E11-106R-007162

Load Capacity (IS)

km/h / bar	5.00
40	2300
50	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..