



IS standard



GROWING TOGETHER

# ROCK SPECIAL L-4



PRODUCT DATA SHEET



Bias



# ROCK SPECIAL L-4

ROCK SPECIAL (L-4) is a bias-ply tyre engineered for loaders operating in severe mining and quarry applications. The extra deep rock pattern delivers excellent traction even under harsh operating conditions, while the wide footprint ensures great stability and operator comfort. ROCK SPECIAL (L-4) features a steel-belted heavy-duty casing and a particularly cut- and-chip-resistant tread compound to provide excellent protection against external damage. The tyre stands out for durability and reduced downtime, making it the ideal choice for the toughest requirements in rocky environments.

**Technologies**



Extra Deep Tread



Reinforced Carcass



Steel Belted

**Performance**



Cut and Chip Resistance



Cut Resistance



Durability



High Puncture Resistance



Stability



Traction

	Tyre size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	26.5 - 25	TL	-	32	-	SB	-	690	1785	-	-	69	22.00/3.0	-
	29.5 - 25	TL	-	34	-	SB	-	780	1880	-	-	73	25.00/3.5	-

SB: Steel Belted



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference