



## RIDEMAX IT 696



### Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	440/80R24IND
LI/SS	154;A8

## Dimensions US Standard

USA Code	94057269
SW (US) (in)	17.4
OD (US) (in)	51.7
SLR (US) (in)	23.2
RC (US) (in)	155.1
Rim Rec	DW 14 L
Rim Alt	DW 15 L; DW 13
ECE	E11-106R-004760

## Load Capacity (US)

mph / psi	17	23	29	35	41	46
40	3370	4160	4870	5670	6380	7160
30	3640	4490	5260	6120	6890	7740
25	3890	4790	5620	6540	7360	8270
20	4660	5750	6750	7840	8830	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..