



MT 612

Description

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ■ Trailer, Industrial & Construction ■
Universal Vehicle



Version STANDARD

Tire Type TT

Tyre size 16.0/70-20

LI/SS

Dimensions IS Standard

SW (IS) (mm)	405
OD (IS) (mm)	1095
SLR (IS) (mm)	520
RC (IS) (mm)	3327
Rim Rec	13.00 T

Load Capacity (IS)

km/h / bar	4.50
80 LS	3075
80 LD	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..