



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 31



PRODUCT DATA SHEET



Radial

E-3/L-3

B

216

Technologies



All Steel



Block Pattern

Performance



Comfort



Traction



Cut Resistance



Stability



Durability



EARTHMAX SR 31

RADIAL OTR TIRES

EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. Its multiple steel belts provide extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. In addition to outstanding riding comfort, EARTHMAX SR 31 features a special tread compound which is particularly cut-and-heat resistant. It provides excellent riding comfort in 'Load and Carry' operations on hard improved surfaces. The radial casing structure also delivers reduced rolling resistance offering significant fuel savings.

Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 25"	20.5 R 25	TL	E-3/L-3	**/*	177 B/ 186 A2	CRC	170	540	1480	663	4449	32	17.00/2.0	-
	23.5 R 25	TL	E-3/L-3	**/*	185 B/ 195 A2	CRC	200	612	1607	711	4797	34	19.50/2.5	-
	26.5 R 25	TL	E-3/L-3	**/*	193 B/ 202 A2	CRC	230	689	1742	766	5200	38	22.00/3.0	-
	26.5 R 25	TL	L-3	**	209 A2	CRC	-	689	1742	766	5200	38	22.00/3.0	-
	29.5 R 25	TL	L-3	**	216 A2	CRC	-	765	1861	818	5555	42	25.00/3.5	-
	29.5 R 25	TL	E-3/L-3	**/*	200 B/ 208 A2	CRC	270	765	1861	818	5555	42	25.00/3.5	-

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference